

Verona - Valerio Catullo Airport

IATA/ICAO CODE:	VRN/LIPX
CITY:	Verona
COUNTRY:	Italy

AIRPORT CONTACT

No changes reported by the airport in 2011
Verify information below with the airport

Name:	ENAC - DA Verona	Aeroporto Valerio Catullo di Verona Villafranca S.p.a.
Title:		
Airport:	Verona - Valerio Catullo Airport	
Address:	37060 Casselle di Sommacampagna Verona Italy	
Phone:	+39 045 8619056 +39 045 8619057	+39 045 8095611
Fax:	+39 045 8619014	
Email:	aero.verona@enac.gov.it	aero.verona@enac.gov.it
Airport Web Site:		

ELEVATION: 240 ft.

RUNWAY INFORMATION				
Orientation	Length (m)	Displaced Threshold (m)	Glide Slope(deg)	Width (m)
04/22	3067.5	-	-	45

NOISE ABATEMENT PROCEDURES

From AIP – Italia ENR 1.5-1 (29 January 2009)

2 NOISE ABATEMENT PROCEDURES (Provision of Italian Civil Aviation Authority N 42/674/A3/4.2 dated March 21st 1996)

2.1 Initial climb procedures

Compliance with the procedures below shall not be required in adverse weather conditions or for safety reasons.

During the initial climb phase pilots shall maintain the following parameters:

- 1) up to 1500 ft QFE:
 - a) take-off power;
 - b) take-off flap
 - c) climb at $V_2 + 10/20$ kt IAS or as limited by body angle;
- 2) at 1500 ft QFE:
 - a) reduce thrust and climb at $V_2 + 10/20$ kt IAS until reaching 3000 ft QFE;

3) at 3000 ft QFE:

2.2 Approach and landing procedures

Pilots shall conduct their flight at a speed which permits operation of the aircraft in clean configuration until reaching a distance of approximately 12 NM from touch down.

Recommended speed is 210 kt \pm 10 kt or the aircraft's minimum performance speed if higher than above.

Subsequent portion of the approach, either instrument or visual, shall be flown with a properly set slope to achieve, if possible, a continuous descent, the interception of approach path not below 3000 ft QFE and aircraft to be established not beyond the OM or equivalent position.

Execution technique must be performed with aircraft deceleration action and aerodynamic configuration change so as to achieve final speed and configuration at the OM, FAF or equivalent position.

Compliance with the above procedure is recommended provided that it is compatible with ATC instructions and weather conditions are favorable.

Non compliance is allowed in case of precision approach CAT II and III.

No instrument or visual approach shall be made at an angle less than the ILS glide path or less than 3° if no ILS is available.

Aircraft executing a visual approach shall intercept descent path at not lower than 1000 ft QFE.

2.3 Provision of Italian Civil Aviation Authority N 42/255/R2/1-9 dated March 17th 1997

Noise abatement procedures described in para 2.1 apply to the following aerodromes: Torino Caselle, Milano Linate, Milano Malpensa, Bergamo, Bologna, Ancona, Forlì (only TKOF RWY 30), Napoli, Pescara, Reggio Calabria (only TKOF RWY 15/33), Rimini, Roma Ciampino, Roma Fiumicino (TKOF RWY 25 excluded), Ronchi (only TKOF RWY 09), Treviso S. Angelo (approved in Treviso AD by local DCA with provision n° 404/2.32 dated 2nd February 2001), **Verona Villafranca** (only TKOF RWY 04/22); **noise abatement procedures described in the above para 2.2 apply to all Italian aerodromes open to civil air traffic.**

The use of the reverse thrust at power higher than idle is allowed only in the event of proven safety/operational reasons.

CONTINUOUS DESCENT ARRIVAL (CDA) - [NONE](#)

AIRPORT CURFEWS - [NONE](#)

PREFERENTIAL RUNWAYS - [NONE](#)

OPERATING QUOTA - [NONE](#)

ENGINE RUN-UP RESTRICTIONS - [NONE](#)

APU OPERATING RESTRICTIONS - [NONE](#)

NOISE BUDGET RESTRICTIONS - [NONE](#)

NOISE SURCHARGE - [NONE](#)

NOISE MITIGATION/LAND USE PLANNING PROGRAM INFORMATION

Type of Program	Date Implemented	Status
Sound Insulation (Residences and Public Buildings)	-	-
Purchase Assurance for Homeowners Located Within the Airport Noise Contours	-	-
Avigation Easements	-	-
Zoning Laws	-	-
Real Estate/Property Disclosure Laws	-	-
Acquire Land for Noise Compatibility to date	-	-
Population within each noise contour level relative to aircraft operations	-	-
Airport Noise Contour Overlay Maps	-	-
Total Cost of Noise Mitigation Programs to Date	-	-
Source of Noise Mitigation Program Funding for Aircraft Noise	-	-

NOISE MONITORING SYSTEM - [NONE](#)

FLIGHT TRACK MONITORING SYSTEM - [NONE](#)

NOISE LEVEL LIMITS - [NONE](#)

CHAPTER 2 RESTRICTIONS

Chapter 2 airplanes >75,000 lbs are banned from operating at airports in EU Member States as of April 1, 2002.

CHAPTER 2 PHASEOUT

From April 1, 2002 all civil subsonic jet aeroplanes >75,000 lbs operating at airports in EU Member States must comply with the standards specified in Part II, Chapter 3, Volume 1 of Annex 16 in accordance with EU Council Directive 92/14/EEC.

CHAPTER 3 RESTRICTIONS - [NONE](#)